



Product	Net storage capacity	Colour
G35 AC/DC Thermoelectric Cooler	approx. 34 litres	Rumba/Dark grey
Voltage	12 V DC, 230 V AC (220 – 240 V) / 50 Hz built-in adapter, Energy class A++	
Insulation	High quality full foam insulation of polyurethane	
Cooling unit	4 A peltier cell with 12 V direct feed or built-in 230 V adapter, cooling max. 18°C below ambient temperature, heating max. 65°C	
Quality features	Car and indoor use with dual voltage system, auto-switch, integrated ABS active battery security, easy access door-in-door bottle compartment, cooling and heating function, fits 2-litre bottles standing, removable divider grid, fold-away side handles for easy carrying	
Dimensions (LxWxH)/weight	54.0 x 35.0 x 44.5 cm / 8.1 kg	
Ref. No.	Packaging	EAN
9105302770	Printed box	4015 7042 0545 9
Pack size	Master pack dimensions (LxWxH)/weight/volume	
1	55.6 x 36.6 x 47.8 cm / 10.5 kg / 0.097 m ³	



Product	Net storage capacity	Colour
T08 DC Thermoelectric Cooler	approx. 8 litres	Metallic blue
Voltage	12 V DC	
Insulation	High quality full foam insulation of polyurethane	
Cooling unit	3 A peltier cell with 12 V feed, cooling max. 20°C below ambient temperature, heating max. 65°C	
Quality features	Specially designed for car use, easy and secure fixing with car seat belt or own shoulder strap, cooling and heating function, fits 0.7-litre bottles lying, cable compartment in lid, single fan system with metal inner case	
Dimensions (LxWxH)/weight	44.0 x 20.0 x 30.0 cm / 3.1 kg	
Ref. No.	Packaging	EAN
9105301856	Printed box	4015 7041 8854 7
Pack size	Master pack dimensions (LxWxH)/weight/volume	Master pack barcode
3	68.5 x 47.8 x 33.8 cm / 13.0 kg / 0.11 m ³	4015 7041 8913 1

Ref. No.	Packaging	EAN
9105301862	Printed box	4015 7041 8854 7
Pack size	Master pack dimensions (LxWxH)/weight/volume	Master pack barcode
8 pieces in display	47.5 x 48.5 x 128.5 cm / 34.5 kg / 0.296 m ³	4015 7041 8914 8



Product	Net storage capacity	Colour
G26 AC/DC Thermoelectric Cooler	approx. 25 litres	Rumba/Dark grey
Voltage	12 V DC, 230 V AC (220 – 240 V) / 50 Hz built-in adapter, Energy class A++	
Insulation	High quality full foam insulation of polyurethane (K-Iso system)	
Cooling unit	4 A peltier cell with 12 V direct feed or built-in 230 V adapter, max. 18°C below ambient temperature	
Quality features	Car and indoor use with dual voltage system, carrier handle serves to either fix or support the lid, cable compartment in lid, fits 2-litre bottles standing, double fan system	
Dimensions (LxWxH)/weight	39.6 x 29.6 x 39.5 cm / 4.0 kg	
Ref. No.	Packaging	EAN
9103500484	Shrink + card	4015 7042 0484 1
Pack size	Master pack dimensions (LxWxH)/weight/volume	Master pack barcode
4	80.0 x 60.0 x 42.0 cm / 18.00 kg / 0.201 m ³	4015 7042 0485 8



Product	Net storage capacity	Colour
Q40 AC/DC Thermoelectric Cooler	approx. 39 litres	Aluminium
Voltage	12 V DC, 230 V AC (220 – 240 V) / 50 Hz built-in adapter, Energy class A++	
Insulation	High quality full foam insulation of polyurethane	
Cooling unit	4 A peltier cell with 12 V direct feed or built-in 230 V adapter, cooling max. 20°C below ambient temperature	
Quality features	Car and indoor use with dual voltage system, sturdy, unbreakable aluminium housing, fold-away side handles, split lid minimize cold loss, cable compartment in lid, fits 2-litre bottles standing, 2 removable divider grids, double fan system	
Dimensions (LxWxH)/weight	58.0 x 39.0 x 44.0 cm / 9.6 kg	
Ref. No.	Packaging	EAN
9105302772	Printed box	4015 7042 0548 0
Pack size	Master pack dimensions (LxWxH)/weight/volume	
1	60.0 x 41.0 x 48.0 cm / 12.2 kg / 0.118 m ³	



Product	Net storage capacity	Colour
G32 AC/DC Thermoelectric Cooler	approx. 29 litres	Rumba/Dark grey
Voltage	12 V DC, 230 V AC (220 – 240 V) / 50 Hz built-in adapter, Energy class A++	
Insulation	High quality full foam insulation of polyurethane (K-Iso system)	
Cooling unit	4 A peltier cell with 12 V direct feed or built-in 230 V adapter, cooling max. 18°C below ambient temperature	
Quality features	Car and indoor use with dual voltage system, carrier handle serves to either fix or support the lid, cable compartment in lid, fits 2-litre bottles standing, double fan system	
Dimensions (LxWxH)/weight	39.6 x 29.6 x 44.5 cm / 4.3 kg	

Ref. No.	Packaging	EAN
9103500485	Shrink + card	4015 7042 0486 5
Pack size	Master pack dimensions (LxWxH)/weight/volume	Master pack barcode
4	80.0 x 60.0 x 46.0 cm / 19.00 kg / 0,220 m ³	4015 7042 0487 2



Product	Net storage capacity	Colour
W40 AC/DC Thermoelectric Cooler	approx. 39 litres	Metallic blue
Voltage	12 V DC, 230 V AC (220 – 240 V) / 50 Hz built-in adapter, Energy class A++	
Insulation	High quality full foam insulation of polyurethane	
Cooling unit	4 A peltier cell with 12 V direct feed or built-in 230 V adapter, cooling max. 18°C below ambient temperature	
Quality features	Car and indoor use with dual voltage system, two sturdy wheels and multi-functional pull-out handle for convenient transport, fold-away side handles, split lid minimize cold loss, cable compartment in lid, fits 2-litre bottles standing, 2 removable divider grids, double fan system	
Dimensions (LxWxH)/weight	56.0 x 38.0 x 42.0 cm / 8.4 kg	

Ref. No.	Packaging	EAN
9105302773	Printed box	4015 7042 0549 7
Pack size	Master pack dimensions (LxWxH)/weight/volume	
1	59.5 x 40.0 x 45.0 cm / 10.8 kg / 0.107 m ³	

Product	Net storage capacity	Colour
W24 AC/DC Thermoelectric Cooler	approx. 20 litres	Metallic blue
Technical data as for P24 AC/DC		
Quality features	Car and indoor use with dual voltage system, carrier handle serves to either fix or support the lid, cable compartment in lid, fits 2-litre bottles standing, double fan system, pull-out handle and sturdy wheels, cooling and heating function	
Dimensions (LxWxH)/weight	39.0 x 28.0 x 42.0 cm / 5.5 kg	

Ref. No.	Packaging	EAN
9103500263	Printed box	4015 7041 9570 5
Pack size	Master pack dimensions (LxWxH)/weight/volume	
1	39.5 x 29.0 x 44.5 cm / 6.1 kg / 0.051 m ³	

